



Multi-Split Cassette Indoor Unit

CODE			27	37	45
Performance					
Indoor Unit		RAS-	M10U2MUVG-E	M13U2MUVG-E	M16U2MUVG-E
Capacity Code			10	13	16
Nominal	Cooling Capacity	kW	2.7	3.7	4.5
	Heating Capacity	kW	4.0	5.0	5.5
UK	Cooling Total/Sensible	kW	2.44/2.03	3.42/2.74	4.49/3.56
	Heating	kW	2.05	2.61	3.53
Cooling EN14825	Range Min. - Max.	kW	1.3 - 3.2	1.3 - 4.1	1.5 - 5.3
	Power Input	kW	0.023	0.023	0.023
Heating EN14825	Range Min. - Max.	kW	0.9 - 4.8	1.0 - 5.3	1.1 - 6.5
	Power Input	kW	0.023	0.023	0.023
Indoor Data					
Air Flow	High - Low	l/s	164 - 119	172 - 119	189 - 125
	High - Low	m ³ /h	590 - 430	620 - 430	680 - 450
Sound	Pressure High - Low	dB(A)	37 - 30	38 - 30	40 - 31
	Power High - Low	dB(A)	52 - 45	53 - 45	55 - 46
Unit	Height x Width x Depth	mm	268 x 575 x 575	268 x 575 x 575	268 x 575 x 575
	Weight	kg	15	15	15
Panel	Height x Width x Depth	mm	27 x 700 x 700	27 x 700 x 700	27 x 700 x 700
	Weight	kg	3	3	3
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4	3/8 - 1/4	1/2 - 1/4
	Drain Pipe Connection OD/ID	mm	32/25	32/25	32/25

Accessories

RB-RXS31-E	Remote Controller Built-In Timer	Weekly-timer, single combination	
RBC-AX32UM(W)-E	Remote Controller Built-In Timer	Infra-red IMS combination	
RB-RWS21E	Remote Controller	Hard-wired remote controller RAS cassette and ducted	
TCB-SIR41UM-E	Occupancy Sensor	Movement sensor control with 10 m diameter detection	
RBC-IS-IR-WIFI-1	WIFI Controller	IntesisHome Wi-Fi Universal Controller	