



Multi-Split Mirai High-Wall Indoor Unit

CODE			15	20	27	37	45
Performance							
Indoor Unit		RAS-	B05BKVG-E	B07BKVG-E	B10BKVG-E	B13BKVG-E	B16BKVG-E
Capacity Code			5	7	10	13	16
Nominal	Cooling Capacity	kW	1.5	2.0	2.7	3.7	4.5
	Heating Capacity	kW	2.0	2.7	4.0	5.0	5.5
UK	Cooling Total/Sensible	kW	1.47/1.22	1.95/1.57	2.44/1.93	3.22/2.49	4.49/3.36
	Heating	kW	1.18	1.60	2.03	2.20	3.33
Cooling EN14825	Range Min. - Max.	kW	1.1 - 1.8	1.2 - 2.5	1.3 - 3.2	1.3 - 4.1	1.5 - 5.3
	Power Input	kW	0.029	0.031	0.033	0.034	0.045
Heating EN14825	Range Min. - Max.	kW	0.9 - 2.5	0.9 - 3.4	0.9 - 4.8	1.0 - 5.3	1.1 - 6.5
	Power Input	kW	0.040	0.040	0.031	0.035	0.031
Indoor Data							
Air Flow	High - Low	l/s	145 - 65	148 - 65	153 - 67	172 - 73	213 - 92
	High - Low	m ³ /h	522 - 234	534 - 234	552 - 240	618 - 264	768 - 330
Sound	Pressure High - Low	dB(A)	37 - 22	38 - 23	39 - 24	42 - 24	43 - 25
	Power High - Low	dB(A)	52 - 37	53 - 38	54 - 39	56 - 39	58 - 40
Unit	Height x Width x Depth	mm	293 x 798 x 230	293 x 798 x 230	293 x 798 x 230	293 x 798 x 230	293 x 798 x 230
	Weight	kg	9	9	9	9	10
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4	3/8 - 1/4	3/8 - 1/4	3/8 - 1/4	1/2 - 1/4
	Drain Pipe Connection OD/ID	mm	16/14	16/14	16/14	16/14	16/14
Remote Controller			WH-UA01NE (Infra-Red)	WH-UA01NE (Infra-Red)	WH-UA01NE (Infra-Red)	WH-UA01NE (Infra-Red)	WH-UA01NE (Infra-Red)

Accessories

RB-RXS30-E	Remote Controller Built-In Timer	Weekly-timer, single combination	
RB-N101S-G	WiFi Controller	WiFi adapter	
RB-N102S-G	WiFi Controller	WiFi adapter and cable	