



VRF 1-Way Cassette Indoor Unit

CODE			22	28	36	45	56	71
Performance								
Indoor Unit		MMU-	AP0074YH1-E	AP0094YH1-E	AP0124YH1-E	AP0154SH1-E	AP0184SH1-E	AP0244SH1-E
Capacity Code		hp	0.8	1.0	1.25	1.7	2.0	2.5
Nominal	Cooling Capacity	kW	2.2	2.8	3.6	4.5	5.6	7.1
	Heating Capacity	kW	2.5	3.2	4.0	5.0	6.3	8.0
UK	Cooling Total/Sensible	kW	2.0/1.7	2.5/2.1	3.3/2.5	4.1/3.0	5.1/3.7	6.4/4.7
	Heating	kW	1.7	2.2	2.7	3.4	4.3	5.4
Electrical	Power Input	kW	0.053	0.053	0.053	0.042	0.046	0.075
	Run Current	A	0.24	0.24	0.24	0.34	0.37	0.62
	Start Current	A	0.60	0.60	0.60	0.51	0.54	0.80
Indoor Data								
Air Flow	High - Medium - Low	l/s	150 - 133 - 117	150 - 133 - 117	150 - 133 - 117	208 - 192 - 175	217 - 200 - 183	317 - 267 - 225
	High - Medium - Low	m ³ /h	540 - 480 - 420	540 - 480 - 420	540 - 480 - 420	750 - 690 - 630	780 - 720 - 660	1140 - 960 - 810
Sound	Pressure High - Medium - Low	dB(A)	42 - 39 - 34	42 - 39 - 34	42 - 39 - 34	37 - 35 - 32	38 - 36 - 34	45 - 41 - 37
	Power High - Medium - Low	dB(A)	57 - 54 - 49	57 - 54 - 49	57 - 54 - 49	52 - 50 - 47	53 - 51 - 49	60 - 56 - 52
Unit	Height x Width x Depth	mm	235 x 850 x 400	235 x 850 x 400	235 x 850 x 400	200 x 1000 x 710	200 x 1000 x 710	200 x 1000 x 710
	Weight	kg	22	22	22	21	21	22
Panel	Height x Width x Depth	mm	18 x 1050 x 470	18 x 1050 x 470	18 x 1050 x 470	20 x 1230 x 800	20 x 1230 x 800	20 x 1230 x 800
	Weight RBC-UW283PG(W)-E	kg	3.5	3.5	3.5	5.5	5.5	5.5
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4	3/8 - 1/4	3/8 - 1/4	1/2 - 1/4	1/2 - 1/4	1/2 - 3/8
	Drain Pipe Connection OD/ID	mm	VP32/25	VP32/25	VP32/25	VP32/25	VP32/25	VP32/25
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5	220-240/1/50-5	220-240/1/50-5	220-240/1/50-5	220-240/1/50-5	220-240/1/50-5

Accessories

RBC-AMT32E	Remote Controller	Full control including service functions
RBC-AMS41E	Remote Controller Built-In Timer	Full control including service functions with fully-programmable 7-day timer
RBC-MTSC1	Mini Touch Screen Controller	Mini touch screen controller with configurable icons
RBC-AMS55E-ES	Remote Controller	Includes timer and backlight display as well as power-save functions, multilingual
RBC-AS41E	Simplified Controller	Ideal for hotel and basic use applications (no service function available)
RBC-ASC11E	Compact Remote Controller	Simplified backlight display controller with timer off, multilingual
RBC-SMCN61	ON/OFF And Locking Lead	Lead to remotely switch a unit ON/OFF and to lock this function
RBC-SMT1	CN02 Connector Timer Interface Lead	Lead to provide ON/OFF control from the RBC-AMT32E remote or any central controller
RBC-AX33CE	Ceiling Receiver	Replacement receiver and remote controller
TCB-TC41LE	Remote Sensor	Room temperature sensing in conditioned space



False ceiling installation



Anti-dust pre-filter



Built-in drain pump



Automatic restart



Louvre control



Multi-split branching