




VRF 4-Way Cassette Indoor Unit

CODE		28	36	45	56	71	
Performance							
Indoor Unit		MMU-	AP0094HP1-E	AP0124HP1-E	AP0154HP1-E	AP0184HP1-E	AP0244HP1-E
Capacity Code		hp	1.0	1.25	1.7	2.0	2.5
Nominal	Cooling Capacity	kW	2.8	3.6	4.5	5.6	7.1
	Heating Capacity	kW	3.2	4.0	5.0	6.3	8.0
UK	Cooling Total/Sensible	kW	2.5/2.0	3.3/2.5	4.1/3.0	5.1/3.8	6.4/4.6
	Heating	kW	2.2	2.7	3.4	4.3	5.4
Electrical	Power Input	kW	0.021	0.021	0.023	0.026	0.036
	Run Current	A	0.23	0.23	0.27	0.29	0.38
	Start Current	A	0.30	0.30	0.33	0.36	0.42
Indoor Data							
Air Flow	High - Medium - Low	l/s	222 - 203 - 188	222 - 203 - 188	258 - 230 - 220	292 - 255 - 222	358 - 255 - 222
	High - Medium - Low	m ³ /h	800 - 730 - 680	800 - 730 - 680	930 - 830 - 790	1050 - 920 - 800	1290 - 920 - 800
Sound	Pressure High - Medium - Low	dB(A)	30 - 29 - 27	30 - 29 - 27	31 - 29 - 27	32 - 29 - 27	35 - 31 - 28
	Power High - Medium - Low	dB(A)	45 - 44 - 42	45 - 44 - 42	46 - 44 - 42	47 - 44 - 42	50 - 46 - 43
Unit	Height x Width x Depth	mm	256 x 840 x 840	256 x 840 x 840	256 x 840 x 840	256 x 840 x 840	256 x 840 x 840
	Weight	kg	20	20	20	20	20
Panel	Height x Width x Depth	mm	30 x 950 x 950	30 x 950 x 950	30 x 950 x 950	30 x 950 x 950	30 x 950 x 950
	Weight RBC-U31PGP(W)-E	kg	4	4	4	4	4
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4	3/8 - 1/4	1/2 - 1/4	1/2 - 1/4	5/8 - 3/8
	Drain Pipe Connection OD/ID	mm	VP32/25	VP32/25	VP32/25	VP32/25	VP32/25
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5	220-240/1/50-5	220-240/1/50-5	220-240/1/50-5	220-240/1/50-5

CODE		80	90	112	140	160	
Performance							
Indoor Unit		MMU-	AP0274HP1-E	AP0304HP1-E	AP0364HP1-E	AP0484HP1-E	AP0564HP1-E
Capacity Code		hp	3.0	3.2	4.0	5.0	6.0
Nominal	Cooling Capacity	kW	8.0	9.0	11.2	14.0	16.0
	Heating Capacity	kW	9.0	10.0	12.5	16.0	18.0
UK	Cooling Total/Sensible	kW	7.3/5.2	8.2/5.9	10.2/7.3	12.7/9.3	14.5/10.4
	Heating	kW	6.1	6.8	8.5	10.9	12.2
Electrical	Power Input	kW	0.036	0.043	0.088	0.112	0.112
	Run Current	A	0.38	0.43	0.73	0.88	0.88
	Start Current	A	0.42	0.59	0.87	1.23	1.26
Indoor Data							
Air Flow	High - Medium - Low	l/s	358 - 255 - 222	367 - 305 - 237	547 - 397 - 297	592 - 397 - 313	592 - 422 - 342
	High - Medium - Low	m ³ /h	1290 - 920 - 800	1320 - 1100 - 850	1970 - 1430 - 1070	2130 - 1430 - 1130	2130 - 1520 - 1230
Sound	Pressure High - Medium - Low	dB(A)	35 - 31 - 28	38 - 33 - 30	43 - 38 - 32	46 - 38 - 33	46 - 40 - 33
	Power High - Medium - Low	dB(A)	50 - 46 - 43	53 - 48 - 45	58 - 53 - 47	61 - 53 - 48	61 - 55 - 48
Unit	Height x Width x Depth	mm	256 x 840 x 840	256 x 840 x 840	319 x 840 x 840	319 x 840 x 840	319 x 840 x 840
	Weight	kg	20	20	25	25	25
Panel	Height x Width x Depth	mm	30 x 950 x 950	30 x 950 x 950	30 x 950 x 950	30 x 950 x 950	30 x 950 x 950
	Weight RBC-U31PGP(W)-E	kg	4	4	4	4	4
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8	5/8 - 3/8	5/8 - 3/8	5/8 - 3/8	5/8 - 3/8
	Drain Pipe Connection OD/ID	mm	VP32/25	VP32/25	VP32/25	VP32/25	VP32/25
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5	220-240/1/50-5	220-240/1/50-5	220-240/1/50-5	220-240/1/50-5

Accessories

RBC-AMT32E	Remote Controller	Full control including service functions
RBC-AMS41E	Remote Controller Built-In Timer	Full control including service functions with fully-programmable 7-day timer
RBC-MTSC1	Mini Touch Screen Controller	Mini touch screen controller with configurable icons
RBC-AMS55E-ES	Remote Controller	Includes timer and backlight display as well as power-save functions, multilingual
RBC-AS41E	Simplified Controller	Ideal for hotel and basic use applications (no service function available)
RBC-ASC11E	Compact Remote Controller	Simplified backlight display controller with timer off, multilingual
RBC-SMCN61	ON/OFF And Locking Lead	Lead to remotely switch a unit ON/OFF and to lock this function
RBC-SMT1	CN02 Connector Timer Interface Lead	Lead to provide ON/OFF control from the RBC-AMT32E remote or any central controller
RBC-AX32U(W)-E	4-Way Cassette Corner	Replacement corner pocket with built-in receiver and remote controller
TCB-TC41LE	Remote Sensor	Room temperature sensing in conditioned space

 False ceiling installation

 Anti-dust pre-filter

 Built-in drain pump

 Automatic restart

 Louvre control

 Multi-split branching

 Individual louvre control