



VRF 4-Way Compact Cassette Indoor Unit

CODE		17	22	28	36	45	56	
Performance								
Indoor Unit		MMU-	AP0057MH-E	AP0077MH-E	AP0097MH-E	AP0127MH-E	AP0157MH-E	AP0187MH-E
Capacity Code		hp	0.6	0.8	1.0	1.25	1.7	2.0
Nominal	Cooling Capacity	kW	1.7	2.2	2.8	3.6	4.5	5.6
	Heating Capacity	kW	1.9	2.5	3.2	4.0	5.0	6.3
UK	Cooling Total/Sensible	kW	1.5/1.3	2.0/1.7	2.5/2.1	3.3/2.5	4.1/3.1	5.1/3.9
	Heating	kW	1.3	1.3	1.7	2.2	2.7	3.4
Electrical	Power Input	kW	0.016	0.023	0.025	0.027	0.030	0.052
	Run Current	A	0.16	0.23	0.24	0.25	0.28	0.46
	Start Current	A	0.28	0.41	0.43	0.44	0.50	0.80
Indoor Data								
Air Flow	High - Medium - Low	l/s	120 - 112 - 102	153 - 128 - 105	158 - 130 - 105	165 - 140 - 112	183 - 153 - 130	233 - 167 - 145
	High - Medium - Low	m ³ /h	430 - 400 - 365	552 - 462 - 378	570 - 468 - 378	594 - 504 - 402	660 - 552 - 468	840 - 642 - 522
Sound	Pressure High - Medium - Low	dB(A)	32 - 30 - 29	37 - 33 - 29	38 - 33 - 29	38 - 34 - 30	40 - 35 - 31	47 - 39 - 34
	Power High - Medium - Low	dB(A)	47 - 45 - 44	52 - 48 - 44	53 - 48 - 44	53 - 49 - 45	55 - 50 - 46	62 - 54 - 49
Unit	Height x Width x Depth	mm	256 x 575 x 575	256 x 575 x 575	256 x 575 x 575	256 x 575 x 575	256 x 575 x 575	256 x 575 x 575
	Weight	kg	15	15	15	15	15	15
Panel	Height x Width x Depth	mm	12 x 620 x 620	12 x 620 x 620	12 x 620 x 620	12 x 620 x 620	12 x 620 x 620	12 x 620 x 620
	Weight RBC-UM21PG(W)-E	kg	2.5	2.5	2.5	2.5	2.5	2.5
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4	3/8 - 1/4	3/8 - 1/4	3/8 - 1/4	1/2 - 1/4	1/2 - 1/4
	Drain Pipe Connection OD/ID	mm	VP26/20	VP26/20	VP26/20	VP26/20	VP26/20	VP26/20
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-3	220-240/1/50-3	220-240/1/50-3	220-240/1/50-3	220-240/1/50-3	220-240/1/50-3

Accessories

RBC-AMT32E	Remote Controller	Full control including service functions
RBC-AMS41E	Remote Controller Built-In Timer	Full control including service functions with fully-programmable 7-day timer
RBC-MTSC1	Mini Touch Screen Controller	Mini touch screen controller with configurable icons
RBC-AMS55E-ES	Remote Controller	Includes timer and backlight display as well as power-save functions, multilingual
RBC-AS41E	Simplified Controller	Ideal for hotel and basic use applications (no service function available)
RBC-ASC11E	Compact Remote Controller	Simplified backlight display controller with timer off, multilingual
RBC-SMCN61	ON/OFF And Locking Lead	Lead to remotely switch a unit ON/OFF and to lock this function
RBC-SMT1	CN02 Connector Timer Interface Lead	Lead to provide ON/OFF control from the RBC-AMT32E remote or any central controller
TCB-PCUC2E	Indoor Control Interface	Application Control Kit
TCB-TC41LE	Remote Sensor	Room temperature sensing in conditioned space



False ceiling installation



Anti-dust pre-filter



Built-in drain pump



Automatic restart



Louvre control



Multi-split branching



Standard 600 x 600 ceiling size