



VRF Floor-Mounted Console Indoor Unit

CODE		22	28	36	45	56	71	
Performance								
Indoor Unit		MML-	AP0074H1-E	AP0094H1-E	AP0124H1-E	AP0154H1-E	AP0184H1-E	AP0244H1-E
Capacity Code		hp	0.8	1.0	1.25	1.7	2.0	2.5
Nominal	Cooling Capacity	kW	2.2	2.8	3.6	4.5	5.6	7.1
	Heating Capacity	kW	2.5	3.2	4.0	5.0	6.3	8.0
UK	Cooling Total/Sensible	kW	2.0/1.3	2.5/1.5	3.3/2.1	3.8/2.5	5.1/3.3	6.4/4.2
	Heating	kW	1.7	2.2	2.7	3.4	4.3	5.4
Electrical	Power Input	kW	0.056	0.056	0.092	0.092	0.102	0.102
	Run Current	A	0.260	0.260	0.430	0.430	0.470	0.470
	Start Current	A	0.60	0.60	0.80	0.80	1.10	1.10
Indoor Data								
Air Flow	High - Medium - Low	l/s	133 - 117 - 100	133 - 117 - 100	250 - 217 - 180	250 - 217 - 180	300 - 267 - 217	300 - 267 - 217
	High - Medium - Low	m ³ /h	480 - 420 - 360	480 - 420 - 360	900 - 780 - 650	900 - 780 - 650	1080 - 930 - 780	1080 - 930 - 780
Sound	Pressure High - Medium - Low	dB(A)	39 - 37 - 35	39 - 37 - 35	45 - 41 - 38	45 - 41 - 38	49 - 44 - 39	49 - 44 - 39
	Power High - Medium - Low	dB(A)	54 - 52 - 50	54 - 52 - 50	60 - 56 - 53	60 - 56 - 53	64 - 59 - 54	64 - 59 - 54
Unit	Height x Width x Depth	mm	630 x 950 x 230	630 x 950 x 230	630 x 950 x 230	630 x 950 x 230	630 x 950 x 230	630 x 950 x 230
	Weight	kg	37	37	37	37	37	37
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4	3/8 - 1/4	3/8 - 1/4	1/2 - 1/4	1/2 - 1/4	5/8 - 3/8
	Drain Pipe Connection OD/ID	mm	VP26/20	VP26/20	VP26/20	VP26/20	VP26/20	VP26/20
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5	220-240/1/50-5	220-240/1/50-5	220-240/1/50-5	220-240/1/50-5	220-240/1/50-5

Accessories

RBC-AMT32E	Remote Controller	Full control including service functions
RBC-AMS41E	Remote Controller Built-In Timer	Full control including service functions with fully-programmable 7-day timer
RBC-MTSC1	Mini Touch Screen Controller	Mini touch screen controller with configurable icons
RBC-AMS55E-ES	Remote Controller	Includes timer and backlight display as well as power-save functions, multilingual
RBC-AS41E	Simplified Controller	Ideal for hotel and basic use applications (no service function available)
RBC-ASC11E	Compact Remote Controller	Simplified backlight display controller with timer off, multilingual
RBC-SMCN61	ON/OFF And Locking Lead	Lead to remotely switch a unit ON/OFF and to lock this function
RBC-SMT1	CN02 Connector Timer Interface Lead	Lead to provide ON/OFF control from the RBC-AMT32E remote or any central controller
TCB-TC41LE	Remote Sensor	Room temperature sensing in conditioned space



Floor-mounted console



Automatic restart



Multi-split branching