



VRF Vertical Ducted Indoor Unit

CODE		22	28	36	45	56	71	
Performance								
Indoor Unit		MMD-	AP0076BHP1-E	AP0096BHP1-E	AP0126BHP1-E	AP0156BHP1-E	AP0186BHP1-E	AP0246BHP1-E
Capacity Code		hp	0.8	1.0	1.25	1.7	2.0	2.5
Nominal	Cooling Capacity	kW	2.2	2.8	3.6	4.5	5.6	7.1
	Heating Capacity	kW	2.5	3.2	4.0	5.0	6.3	8.0
UK	Cooling Total/Sensible	kW	2.0/1.7	2.5/2.2	3.3/2.5	4.1/3.3	5.1/3.8	6.4/4.9
	Heating	kW	1.7	2.2	2.7	3.4	4.3	5.4
Electrical	Power Input	kW	0.038	0.043	0.043	0.062	0.062	0.077
	Run Current	A	0.26	0.29	0.29	0.42	0.42	0.52
	Start Current	A	0.45	0.50	0.50	0.73	0.73	0.90
Indoor Data								
Air Flow	High - Medium - Low	l/s	150 - 125 - 100	158 - 133 - 108	158 - 133 - 108	217 - 183 - 150	217 - 183 - 150	333 - 267 - 242
	High - Medium - Low	m³/h	540 - 450 - 360	570 - 480 - 390	570 - 480 - 390	798 - 660 - 540	798 - 660 - 540	1200 - 990 - 870
External Static Pressure	Standard	Pa	30	30	30	30	30	40
	Upper - Lower	Pa	115 - 30	115 - 30	115 - 30	115 - 30	115 - 30	115 - 30
Sound	Pressure High - Medium - Low	dB(A)	29 - 26 - 23	30 - 26 - 23	30 - 26 - 23	33 - 29 - 25	33 - 29 - 25	36 - 31 - 27
	Power High - Medium - Low	dB(A)	44 - 41 - 38	45 - 41 - 38	45 - 41 - 38	48 - 44 - 40	48 - 44 - 40	51 - 46 - 42
Unit	Height x Width x Depth	mm	750 x 700 x 275	750 x 700 x 275	750 x 700 x 275	750 x 700 x 275	750 x 700 x 275	750 x 1000 x 275
	Weight	kg	23	23	23	23	23	30
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4	3/8 - 1/4	3/8 - 1/4	1/2 - 1/4	1/2 - 1/4	5/8 - 3/8
	Drain Pipe Connection Upper - Lower	mm	VP25 - VP25	VP25 - VP25	VP25 - VP25	VP25 - VP25	VP25 - VP25	VP25 - VP25
	Lift Pump Drain Height from Unit Base	mm	< 850	< 850	< 850	< 850	< 850	< 850
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5	220-240/1/50-5	220-240/1/50-5	220-240/1/50-5	220-240/1/50-5	220-240/1/50-5

CODE		80	90	112	140	160	
Performance							
Indoor Unit		MMD-	AP0276BHP1-E	AP0306BHP1-E	AP0366BHP1-E	AP0486BHP1-E	AP0566BHP1-E
Capacity Code		hp	3.0	3.2	4.0	5.0	6.0
Nominal	Cooling Capacity	kW	8.0	9.0	11.2	14.0	16.0
	Heating Capacity	kW	9.0	10.0	12.5	16.0	18.0
UK	Cooling Total/Sensible	kW	7.3/5.5	8.2/6.1	10.2/7.8	12.7/9.3	14.5/10.3
	Heating	kW	6.1	6.8	8.5	10.9	12.2
Electrical	Power Input	kW	0.077	0.094	0.172	0.198	0.198
	Run Current	A	0.52	0.61	1.07	1.23	1.23
	Start Current	A	0.90	1.06	1.85	2.13	2.13
Indoor Data							
Air Flow	High - Medium - Low	l/s	333 - 267 - 242	350 - 300 - 258	533 - 450 - 383	583 - 483 - 417	583 - 483 - 417
	High - Medium - Low	m³/h	1200 - 990 - 870	1260 - 1110 - 930	1920 - 1620 - 1380	2100 - 1740 - 1500	2100 - 1740 - 1500
External Static Pressure	Standard	Pa	40	40	50	50	50
	Upper - Lower	Pa	115 - 30	115 - 30	115 - 30	115 - 30	115 - 30
Sound	Pressure High - Medium - Low	dB(A)	36 - 31 - 27	36 - 31 - 27	40 - 36 - 33	40 - 36 - 33	40 - 36 - 33
	Power High - Medium - Low	dB(A)	51 - 46 - 42	51 - 46 - 42	55 - 51 - 48	55 - 51 - 48	55 - 51 - 48
Unit	Height x Width x Depth	mm	750 x 1000 x 275	750 x 1000 x 275	750 x 1400 x 275	750 x 1400 x 275	750 x 1400 x 275
	Weight	kg	30	30	40	40	40
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8	5/8 - 3/8	5/8 - 3/8	5/8 - 3/8	5/8 - 3/8
	Drain Pipe Connection Upper - Lower	mm	VP25 - VP25	VP25 - VP25	VP25 - VP25	VP25 - VP25	VP25 - VP25
	Lift Pump Drain Height from Unit Base	mm	< 850	< 850	< 850	< 850	< 850
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-5	220-240/1/50-5	220-240/1/50-5	220-240/1/50-5	220-240/1/50-5

NOTE: RBC-VCK1 VERTICAL CONVERSION KIT REQUIRED

Accessories

RBC-AMT32E	Remote Controller	Full control including service functions
RBC-AMS41E	Remote Controller Built-In Timer	Full control including service functions with fully-programmable 7-day timer
RBC-MTSC1	Mini Touch Screen Controller	Mini touch screen controller with configurable icons
RBC-AMS55E-ES	Remote Controller	Includes timer and backlight display as well as power-save functions, multilingual
RBC-AS41E	Simplified Controller	Ideal for hotel and basic use applications (no service function available)
RBC-ASC11E	Compact Remote Controller	Simplified backlight display controller with timer off, multilingual
TCB-AX32E2	External Receiver	Independent receiver and WH-L11SE remote controller for all models
RBC-SMCN61	ON/OFF And Locking Lead	Lead to remotely switch a unit ON/OFF and to lock this function
RBC-SMT1	CN02 Connector Timer Interface Lead	Lead to provide ON/OFF control from the RBC-AMT32E remote or any central controller
TCB-TC41LE	Remote Sensor	Room temperature sensing in conditioned space
TCB-SF56C6BPE	Discharge Spigot 2 x 200 mm	MMD-AP007#-018#HP1-E
TCB-SF80C6BPE	Discharge Spigot 3 x 200 mm	MMD-AP024#-030#BHP1-E
TCB-SF160C6BPE	Discharge Spigot 4 x 200 mm	MMD-AP036#-056#BHP1-E



Concealed false ceiling installation



Built-in drain pump



Automatic restart



Multi-split branching